



I-TRONIK S.R.L. - Macchine e prodotti per l'industria elettronica Via dell'Artigianato, 20 - 35010 - Peraga di Vigonza (PD) Tel. +39.049.895.2300 - Fax +39.049.893.4822 - P.IVA 01443020282 commerciale@itronik.it _ www.itronik.it





Miniature Profling Datalogger



6 Channel Thermocouple Adapter

SolderStar PRO - 6 Channel Reflow Profiling System

Designed for manufacturers and EMS providers looking for the ultimate in temperature profiling, the SolderStar Pro package takes profiling capability to the highest level and provides true process profiling for optimum quality control.

The SolderStar Pro includes the ultra compact Neptune SL datalogger with unique 'SmartLink' connector system. The 'SmartLink' concept allows high measurement channel configurations. while maintaining a small footprint and connection to a range of accessories for capture of SPC information from both reflow and wave soldering processes.

A comprehensive suite of full-feature software includes profile simulations and integrated SPC charting tools. This easy to use system is ideal for manufacturers and EMS providers who profile periodically to form a complete mass soldering quality control tool.

System Advantages

- Datalogger provides industry-leading accuracy, slim-line footprint and full lead-free thermal performance
- Support for 6 to 16 measurement channels for profiling of the most complex PCB assemblies
- Unique SmartLink connection system provides easy and flexible connection to a range of products and accessories
- Professional software tools including profile analysis and simulation, ISO documentation and integrated SPC management software
- Connectivity via standard USB cables or 2.4Ghz Wireless Telemetry
- DeltaProbe and Wave Shuttle accessorties extend the dataloggers use for wave solder process control and reflow oven performance monitoring



Size/Weight

Datalogger

125mm x 52mm x 9mm,110g

Technical Data

Channels 6,9,12 or 16 Channel Versions Available

Memory 120,000 Memory Points

Sampling 0.1 - 10 Minutes

Measurement Range -150 - 500 °C

Accuracy ±1 °C

Resolution ±0.02 °C

Max. Internal Temperature +85 °C (Auto Shutdown on over temp.)

Power Rechargeable High Temperature Nimh

Communications USB (Type A - Mini B) or 2.4Ghz Wireless

Thermocouples Type K, Special limits of error.

EN 05842:1993 Class 1 / ANSI MC 96.1

Heatshield + Thermocouple Adapter

Supplied Model HS2580-SL + SL-HS-6


Material Stainless Steel

Size (LxWxH)

6/9 Channel Version: 330mm x 80mm x 25mm
12 Channel Version: 330mm x 104mm x 25mm

16 Channel Version: 330mm x 146mm x 25mm

Thermal Protection Duration



Other heatshield sizes are available for special process requirements.

Wireless Telemetry Option

Frequency 2.4GHZ Transceiver

Channels 128 Individual Channels

Protocol Zigbee PRO - Duplex Transmission

Software

Compatibility Windows™ XP Vista/Windows 7 32 & 64 Bit

Language Support English, French, German, Italian, Korean,

Portuguese, Spanish, Simplified &

Traditional Chinese

Application Areas

- Reflow Soldering
- Wave Soldering
- BGA & uBGA profiling
- Wave Solder & Reflow Process Control (SPC)
- Glue Cure
- Batch Vapour Phase

Standard Equipment

- Neptune SL USB datalogger
- 6 Channel Thermocouple Adapter
- 25mm Lead Free heatshield
- 6 Type K thermocouples
- Profile Central PC Analysis software
- Profile Seeker Simulation + SPC Manager tools
- Reflow oven and solder paste libraries
- Hard copy manual + 1 Year calibration certificate
- Equipment case

Optional Equipment

- AUTOSeeker Profiler Optimisation software
- 9,12 or 16 Channel Adapter
- 2.4Ghz Wireless Telemetry
- WaveShuttle Pro Wave Solder Analyser & SPC fixture
- DeltaProbe Reflow oven performance fixture
- Vapour Phase Shield
- Adjustable Reflow Carrier

Specification subject to change without notification



REFLOW • WAVE • VAPOUR

SolderStar Ltd Manchester UK

Tel: +44 (0)1706 354846 Fax: +44 (0)1706 675296 Email: info@solderstar.com www.solderstar.com

For further information and demonstration software visit www.solderstar.com